3300 liter tank i Syrafast 316



79 000 SEK /st exkl moms

Article type: brand new storage tank - type K-SL
Volumetric volume (L): 3.300 L
Max. density P (kg/m³): 1.150
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: conical 18 °
Shape of tank: cylindrical
Bottom type: conical 18 °
Total discharge: yes
Fixation points: 4 adjustable feet

Legs: Set of baseplates and adjusting pieces included
Manway(s): RVS 316
Gasket manway(s): parra rubber
Valve: RVS 316L
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no

Number of manways: 1
Position of manway: headside
Height manhole 1 (mm): 500 mm
Hinged lid: yes
CIP spray ball: no

Tank outlet: inside Ø 65 mm
Outlet type: DIN11851 male
Total outlet valve: no, optional
Adjustable legs: yes
Agitator: no, optional

Top: 1,50 mm
Cylinder: 1,50 mm
Bottom: 3 mm
Internal diameter tank: 1.592 mm
Distance from outlet to ground: 230 mm

Outer diameter tank: 1.595 mm
Cylinder height: 1.500 mm
Feet height: 570 mm
Total height of tank: 2.500 mm

Empty weight tank: 200

SKU: 374909

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Maximal densitet för produkten: 1150
Mobil tank: Nej
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical 18 °
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 3300

Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 65 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851 male

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 1.500 mm
Höjd på fötter: 570 mm
Invändig diameter: 1.592 mm
Mått utlopp till marken: 230 mm
Total höjd: 2.500 mm
Ytterdiameter: 1.595 mm

Tjocklek på tank

Botten: 3 mm
Cylinder: 1,50 mm
Topp: 1,50 mm

Mer

Isolerad: Nej
Vikt: 200