

3300 liter tank i Rostfritt 304



105,000,00 kr /st exkl moms

Additional information: Pharmacy; Double jacket with electric plug-in heater: 9 kW (functionality not guaranteed) around the lower cylinder area and the lower floor; height-adjustable foot-frame, Aisi 304; Internal fittings (e.g. welded brackets) inside the tank

Volumetric volume (L): 3.300 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Position of manway: cylinder
Outlet of tank: DN50 DIN 11851
Agitator: yes

Number of revolutions: 5.7 - 40
Power: 1,10
Internal diameter tank: 1.480 mm
Outer diameter tank: 1.650 mm
Cylinder height: 1.950 mm

Total height of tank: 3.450 mm

SKU: 291113

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: Pharmacy; Double jacket with electric plug-in heater: 9 kW (functionality not guaranteed) around the lower cylinder area and the lower floor; height-adjustable foot-frame, Aisi 304; Internal

Övrig information2: fittings (e.g. welded brackets) inside the tank; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3300

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.950 mm

Invändig diameter: 1.480 mm

Total höjd: 3.450 mm

Ytterdiameter: 1.650 mm



Omrörare

Kraft (kW): 1,10

Varvtal: 5.7 - 40

Mer

Värmeväxlare: RVS 304

Isolerad: Ja