3300 liter tank i Rostfritt 304



45 000 SEK /st exkl moms

Article type: second-hand storage tank
Volumetric volume (L): 3.300 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: horizontal

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Shape of tank: cylindrical

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Wall type: dished
Total discharge: yes
Fixation points: 4 adjustable feet
Insulation material: PUR
Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 470 mm
Tank outlet: inside Ø 50 mm

Outlet type: DIN11851
Total outlet valve: yes
Internal diameter tank: 1.400 mm
Distance from outlet to ground: 60 mm
Outer diameter tank: 1.500 mm

Cylinder height: 2.220 mm
Total height of tank: 1.700 mm
Total outer length: 2.700 mm
Empty weight tank: 600

SKU: 573287

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: insulated
Mobil tank: Nej
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Yes
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 3300

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851
Utloppsventil: Ja

Översikt material

Material: Rostfritt 304
Isoleringsmaterial: PUR
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 2.220 mm
Invändig diameter: 1.400 mm
Mått utlopp till marken: 60 mm
Total höjd: 1.700 mm
Ytterdiameter: 1.500 mm

Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: PUR

Mer

Isolerad: Ja
Vikt: 600