

3400 liter tank i Rostfritt 304



81,000,00 kr /st exkl moms

Additional information: Pharmacy; 2 longitudinal sight glasses in the cylinder; some residues of previous content; bump at the insulation jacket

Volumetric volume (L): 3.400 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 190 L

Max Overpressure: 0,50 Bar

Max. working temperature: 110 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 15 / 30

Power: 4 / 6

Internal diameter tank: 1.590 mm

Outer diameter tank: 1.750 mm

Cylinder height: 1.500 mm

Total height of tank: 4.150 mm

SKU: 482146

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Pharmacy; 2 longitudinal sight glasses in the cylinder; some residues of previous content;bump at the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't give

Övrig information2: any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3400

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 1.590 mm
Total höjd: 4.150 mm
Ytterdiameter: 1.750 mm

Omrörare

Kraft (kW): 4 / 6
Varvtal: 15 / 30

Mer

Isolerad: Ja