343 liter tank i Syrafast 316



57 000 SEK /st exkl moms

Additional information: Various technical documents (mostly in Polish) are available
Volumetric volume (L): 343 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 25
Top: 3,20 mm
Cylinder: 3 mm

Bottom: 2,60 mm
Internal diameter tank: 740 mm
Cylinder height: 595 mm
Total height of tank: 1.750 mm

SKU: 705775

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Various technical documents (mostly in Polish) are available
Omrörare: Nej
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 343

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 595 mm
Invändig diameter: 740 mm
Total höjd: 1.750 mm

Tjocklek på tank
Botten: 2,60 mm
Cylinder: 3 mm
Topp: 3,20 mm

Mer
Isolerad: Nej