3450 liter tank i Syrafast 316



89 000 SEK /st exkl moms

Additional information: 4 stainless steel lugs; the insulation and insulation jacket were extensively cut open during disassembly and are missing in large sections; 1 overflow pipe inside the tank (see photos); insulation is not shown in the drawing of a similar tank
Volumetric volume (L): 3.450 L
Pressure in tank: pressure

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 80 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 150 L
Max Overpressure: 6 Bar
Max. working temperature: 80 °C
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN65

Top: 4 mm
Cylinder: 4 mm
Bottom: 4 mm
Internal diameter tank: 1.592 mm
Cylinder height: 1.340 mm

Total height of tank: 3.100 mm

SKU: 709396

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: insulated
Max. arbetstemperatur: 80 °C
Mobil tank: Nej
Övrig information: 4 stainless steel clamps; the insulation and insulation jacket were extensively cut open during disassembly and are missing in large sections; 1 overflow pipe inside the vessel (see photos)
Övrig information2: is not shown in the drawing of a similar tank
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 3450

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.340 mm
Invändig diameter: 1.592 mm
Total höjd: 3.100 mm

Tjocklek på tank
Botten: 4 mm
Cylinder: 4 mm
Topp: 4 mm

Mer
Isolerad: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se