

## 3500 liter tank i Rostfritt 304



**116 000 SEK /st exkl moms**

**Additional information:** chemistry; Armaflex-insulation on the tank cover and the upper cylindrical area (see pictures); some residues of previous content

**Volumetric volume (L):** 3.500 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 4 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 120 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 320 L

**Max Overpressure:** 4 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 15 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** flange DN50

**Agitator:** yes

**Number of revolutions:** 395

**Power:** 6,80

**Internal diameter tank:** 1.580 mm

**Outer diameter tank:** 1.660 mm

**Cylinder height:** 1.700 mm

**Total height of tank:** 4.550 mm

**SKU:** 270670

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 120 °C

Mobil tank: Nej

Övrig information: chemistry; Armaflex-insulation on the tank cover and the upper cylindrical area (see pictures); some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3500

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304



## **Dimensioner av tank**

Cylinderhöjd: 1.700 mm  
Invändig diameter: 1.580 mm  
Total höjd: 4.550 mm  
Ytterdiameter: 1.660 mm

## **Omrörare**

Kraft (kW): 6,80  
Varvtal: 395

## **Mer**

Isolerad: Nej