3500 liter tank i Rostfritt 304

81 000 SEK /st exkl moms

Additional information: Beverage industry; Minor dents on feet and spout; dome screws of the feet and tommy screw of the manhole cover missing; some residues of previous content; bump at the insulation jacket
Volumetric volume (L): 3.500 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Position of manway: headside
Outlet of tank: DN80 DIN 11851
Agitator: yes
Power: 2,20

Internal diameter tank: 1.590 mm
Outer diameter tank: 1.770 mm
Cylinder height: 1.500 mm
Total height of tank: 4.250 mm

SKU: 418262

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: Beverage industry; Smaller dents on feet and outlet; the hight adjustable screws of the feet and the toggle screw of the manhole cover are missing ; some residues of previous content;bump at the
Övrig information2: insulation jacket; we can’t give any guarantees about the heating/cooling jacket; we can’t give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 3500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 1.590 mm
Total höjd: 4.250 mm
Ytterdiameter: 1.770 mm

Omrörare
Kraft (kW): 2,20

Mer
Isolerad: Ja