

3500 liter tank i Syrafast 316



80 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; 3 feet, Fe screwed to st. st. support brackets; Manhole diameter approx. 420 mm (most of the manhole cover screws are missing); some residues of previous content

Volumetric volume (L): 3.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 2 Bar

Max onderdruk: 1 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 53

Internal diameter tank: 1.585 mm

Cylinder height: 1.300 mm

Total height of tank: 2.850 mm

SKU: 284272

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry ; 3 feet, Fe screwed to st. st. support brackets;

Manhole diameter approx. 420 mm (most of the manhole cover screws are missing); some residues of previous content

Omrörare: Nej

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.300 mm

Invändig diameter: 1.585 mm

Total höjd: 2.850 mm

Mer

Isolerad: Nej
