

3500 liter tank i Syrafast 316



118,000,00 kr /st exkl moms

Additional information: Pharmaceutical chemistry; 3 support brackets, Aisi 304; double jacket for heating/cooling around the lower cylinder area and the lower bottom (double jacket was added later and is not shown in the vessel drawing); slight differences in the design of the two vessels, e.g. differences in the manhole covers and the outlets (1 x outlet diameter approx. 53 mm, 1 x outlet diameter approx. 210 mm);

see photos); Insulation no longer available

Volumetric volume (L): 3.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 160 L

Max Overpressure: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Top: 7 mm

Cylinder: 6 mm

Bottom: 5,10 mm

Internal diameter tank: 1.600 mm

Outer diameter tank: 1.690 mm

Cylinder height: 1.300 mm

Total height of tank: 2.500 mm

Empty weight tank: 800

SKU: 453239

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; 3 support brackets, Aisi 304; double jacket for heating/cooling around the lower cylinder area and the lower bottom (double jacket was added later and is not shown in the

Övrig information2:

Omrörare: Nej

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.300 mm

Invändig diameter: 1.600 mm

Total höjd: 2.500 mm

Ytterdiameter: 1.690 mm

Tjocklek på tank

Botten: 5,10 mm

Cylinder: 6 mm

Topp: 7 mm

Mer

Värmeväxlare: RVS 316

Isolerad: Nej

Vikt: 800