

3500 liter tank i Syrafast 316



109 000 SEK /st exkl moms

Additional information: rennet-production; Feet originally stood on load cells, these are no longer present (see photos); according to the rating plate, the heating coil is designed for an operating pressure of 3 bar at a temperature of - 5° C (see photos on rating plate); manhole diameter 430 mm; suspension of the manhole cover incomplete

Volumetric volume (L): 3.500 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Volume: 62 L
Max Overpressure: 3 Bar
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Heat exchanger: RVS 304
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: DN40 DIN 11851

Agitator: yes
Number of revolutions: 910
Power: 0,55
Internal diameter tank: 1.350 mm
Outer diameter tank: 1.560 mm

Cylinder height: 2.500 mm
Total height of tank: 3.450 mm

SKU: 270919

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: rennet-production; Feet originally stood on load cells, these are no longer available (see pictures); according to the type plate, the heating coil is designed for an operating pressure of 3 bar at

Övrig information2: temperature of - 5° C (see photos on rating plate); manhole diameter 430 mm; suspension of the manhole cover incomplete; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.500 mm
Invändig diameter: 1.350 mm
Total höjd: 3.450 mm
Ytterdiameter: 1.560 mm

Omrörare

Kraft (kW): 0,55
Varvtal: 910

Mer

Värmeväxlare: RVS 304
Isolerad: Ja