

3500 liter tank i Syrafast 316



109,000,00 kr /st exkl moms

Additional information: rennet-production; Feet originally stood on load cells, these are no longer available (see pictures); according to the type plate, the heating coil is designed for an operating pressure of 3 bar at a temperature of - 5 ° C (see photos on the type plate); diameter manhole 430 mm; suspension of manhole cover incomplete

Volumetric volume (L): 3.500 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 62 L

Max Overpressure: 3 Bar

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN40 DIN 11851

Agitator: yes

Number of revolutions: 910

Power: 0,55

Internal diameter tank: 1.350 mm

Outer diameter tank: 1.560 mm

Cylinder height: 2.500 mm

Total height of tank: 3.450 mm

SKU: 270919

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: rennet-production; Feet originally stood on load cells, these are no longer available (see pictures); according to the type plate, the heating coil is designed for an operating pressure of 3 bar at

Övrig information2:

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 2.500 mm
Invändig diameter: 1.350 mm
Total höjd: 3.450 mm
Ytterdiameter: 1.560 mm

Omrörare

Kraft (kW): 0,55
Varvtal: 910

Mer

Värmeväxlare: RVS 304
Isolerad: Ja