

35000 liter tank i Syrafast 316



202 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: Equipped with 1 compartment.

Volumetric volume (L): 35.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316L (V4A)

Model: horizontal

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Wall type: dished

Total discharge: yes



Fixation points: saddles

Manway(s): RVS 316

Gasket manway(s): unknown

Fixation point(s): steel-epoxy

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 3

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Position 2nd manway: at the top

Height manhole 2 (mm): 500

CIP spray ball: no

Tank outlet: inside Ø 80 mm

Total outlet valve: yes

Agitator: no

Top: 5 mm

Cylinder: 5 mm

Bottom: 5 mm

Outer diameter tank: 2.500 mm

Total height of tank: 2.950 mm

Total outer length: 8.400 mm

Empty weight tank: 6.000

SKU: 9332

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Horisontell
Nyttillverkad/Begagnad: Begagnad
Arbetsstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Equipped with 1 compartment.
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 35000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 80 mm
Teknisk ritning finns: Nej
Utloppsventil: Ja

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): steel-epoxy



Dimensioner av tank

Total höjd: 2.950 mm

Ytterdiameter: 2.500 mm

Tjocklek på tank

Botten: 5 mm

Cylinder: 5 mm

Topp: 5 mm

Mer

Isolerad: Nej

Vikt: 6.000