

3532 liter tank i Syrafast 316



167 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; 3 claws made of Fe; half-pipe coil around the lower cylinder area; 1 heating connection probably slightly bent; bump at the insulation jacket; manhole cover plated

Volumetric volume (L): 3.532 L

Pressure in tank: vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 103 L

Max Overpressure: 16 Bar

Max. working temperature: 100 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Number of revolutions: 313

Power: 1,10

Internal diameter tank: 1.590 mm

Outer diameter tank: 1.800 mm

Total height of tank: 3.300 mm

Empty weight tank: 1.450

SKU: 273976

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry; 3 support brackets made of Fe; half-coil around the lower cylinder area; 1 heating connection probably slightly bent ; bump at the insulation jacket;manhole cover plated;

Övrig information2: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3532

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.590 mm

Total höjd: 3.300 mm

Ytterdiameter: 1.800 mm

Omrörare

Kraft (kW): 1,10

Varvtal: 313

Mer

Värmeväxlare: RVS 304

Isolerad: Ja

Vikt: 1.450