3533 liter tank i Rostfritt 304



109 000 SEK /st exkl moms

Additional information: Double jacket with electric plug-in heater : 9 kW (incomplete; no guarantee of functionality); presumably the lower cylinder area of the vessel can also be heated; manhole approx. 310 x 420 mm; internal fittings (e.g. welded tabs) inside the tank; some residues of previous content
Volumetric volume (L): 3.533 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 50 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 553 L
Max. working temperature: 50 °C
Type HE on the bottom: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder

Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 76
Power: 1,50
Internal diameter tank: 1.490 mm

Outer diameter tank: 1.650 mm
Cylinder height: 1.980 mm
Total height of tank: 3.200 mm

SKU: 414359

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 50 °C
Mobil tank: Nej
Övrig information: Pharmacy; Double jacket with electric plug-in heater: 9 kW (incomplete; functionality not guaranteed); presumably the lower cylinder area of the tank can also be heated; manhole approx. 310 x 420
Övrig information2: 420 mm; internal fittings (e.g. welded tabs) inside the tank; some residues of previous content; we can’t give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 3533

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 1.980 mm
Invändig diameter: 1.490 mm
Total höjd: 3.200 mm
Ytterdiameter: 1.650 mm

Omrörare
Kraft (kW): 1,50
Varvtal: 76

Mer
Värmeväxlare: RVS 304
Isolerad: Ja