

35895 liter tank i Syrafast 316



297,000,00 kr /st exkl moms

Article type: second-hand pressure tank

Volumetric volume (L): 35.895 L

Pressure in tank: pressure

Design pressure (Bar): 10 Bar

Max. pressure (Bar): 4 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 316L (V4A)

Model: horizontal

Configuration: insulated



Heat exchanger: no

Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Wall type: dished

Total discharge: yes

Fixation points: non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 316

Gasket manway(s): unknown

Valve: RVS 316L

Gasket shut-off valve (mat): unknown

Fixation point(s): painted steel

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: at the top

Tank outlet: inside Ø 100 mm

Total outlet valve: yes

Top: 6 mm

Cylinder: 6 mm

Bottom: 6 mm

Insulation top: yes

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: riveted

Insulation thickness: 100

Internal diameter tank: 2.200 mm

Distance from outlet to ground: 100 mm

Outer diameter tank: 2.400 mm



Total height of tank: 2.850 mm

Total outer width: 2.450 mm

Total outer length: 10.400 mm

Empty weight tank: 12.000

SKU: 11967

Mer information
