

3600 liter tank i Syrafast 316



112 000 SEK /st exkl moms

Additional information: Food industry; Operating pressure for steam operation of the double jacket 1 bar;
1 height-adjustable screw is missing from 1 tank

Volumetric volume (L): 3.600 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 100 L

Max Overpressure: 4 Bar

Max. working temperature: 100 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 95

Agitator: yes

Number of revolutions: 19.5 / 40

Power: 1.1 / 1.8

Internal diameter tank: 1.600 mm

Outer diameter tank: 1.750 mm

Cylinder height: 1.500 mm

Total height of tank: 3.350 mm

SKU: 286964

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfERIC

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Food industry; Operating pressure for steam operation of the double jacket 1 bar; 1 height-adjustable screw is missing from 1 tank; we can't give any guarantees about the heating/cooling jacket; we

Övrig information2: can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3600

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 1.600 mm
Total höjd: 3.350 mm
Ytterdiameter: 1.750 mm

Omrörare

Kraft (kW): 1.1 / 1.8
Varvtal: 19.5 / 40

Mer

Isolerad: Ja