

36000 liter tank i Rostfritt 304



213,000,00 kr /st exkl moms

Additional information: Brewery; 1 manhole approx. 360 x 440 mm in the front bottom; 3 loose bearing saddles each made of Fe (galvanized); 1 cut-off connection diameter 100 mm at the bottom of the cylinder; 1 tank with a larger dent in the cylinder/bottom transition as well as several smaller dents; 1 other tank with dents in the cylinder (see photos); some residues of previous content

Volumetric volume (L): 36.000 L

Pressure in tank: pressure

Max. pressure (Bar): 2 Bar

Material wet parts: SS AISI 304 (V2A)

Model: horizontal

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN100 DIN 11851

Cylinder: 2,80 mm

Bottom: 4,80 mm

Internal diameter tank: 3.290 mm

Outer diameter tank: 3.300 mm

Total outer length: 5.000 mm

SKU: 314921

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Brewery; 1 manhole approx. 360 x 440 mm in the front bottom; 3 loose bearing saddles each made of Fe (galvanized); 1 cut-off connection diameter 100 mm at the bottom of the cylinder; 1 tank with a

Övrig information2: larger dent in the cylinder/bottom transition as well as several smaller dents; 1 other tank with dents in the cylinder (see photos); some residues of previous content

Omrörare: Nej

Övertryck: 2 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 36000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 3.290 mm

Ytterdiameter: 3.300 mm

Tjocklek på tank

Botten: 4,80 mm

Cylinder: 2,80 mm

Mer

Isolerad: Nej