36000 liter tank i Rostfritt 304



212 000 SEK /st exkl moms

Additional information: 1 manhole approx. 360 x 440 mm in the front floor; 3 loose bearing saddles each made of Fe (galvanized); 1 cut-off connection diameter 100 mm at the bottom of the vessel; 1 vessel with a stronger dents in the transition cylinder/bottom as well as several smaller dents; 1 further tank with dents in the cylinder (see photos); some residues of previous content
Volumetric volume (L): 36.000 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: pressure
Max. pressure (Bar): 2 Bar
Min. pressure (Bar): 2 Bar

Material wet parts: SS AISI 304 (V2A)
Model: horizontal
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: DN100 DIN 11851
Cylinder: 2,80 mm
Bottom: 4,80 mm
Internal diameter tank: 3.290 mm

Outer diameter tank: 3.300 mm
Total outer length: 5.000 mm

SKU: 435164

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Övrig information: Brewery; 1 manhole approx. 360 x 440 mm in the front bottom; 3 loose bearing saddles each made of Fe (galvanized); 1 cut-off connection diameter 100 mm at the bottom of the cylinder; 1 tank with a
Övrig information2: larger dent in the cylinder/bottom transition as well as several smaller dents; 1 other tank with dents in the cylinder (see photos); some residues of previous content
Omrörare: Nej
Övertryck: 2 Bar
Total urtappning: Ja
Undertryck (vakuum): 2 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 36000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 3.290 mm
Ytterdiameter: 3.300 mm

Tjocklek på tank
Botten: 4,80 mm
Cylinder: 2,80 mm

Mer
Isolerad: Nej