

3640 liter tank i Syrafast 316



188,000,00 SEK /st exkl moms

Additional information: Chemistry; some residues of previous content

Volumetric volume (L): 3.640 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,49 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 2.000 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 132 L

Max Overpressure: 10 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Number of revolutions: 194

Power: 5

Internal diameter tank: 1.600 mm

Cylinder height: 1.450 mm

Total height of tank: 3.500 mm

Empty weight tank: 1.600

SKU: 569045

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 2.000 °C

Mobil tank: Nej

Övrig information: Chemistry; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 0,49 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3640

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.450 mm
Invändig diameter: 1.600 mm
Total höjd: 3.500 mm

Omrörare

Kraft (kW): 5
Varvtal: 194

Mer

Isolerad: Ja
Vikt: 1.600