

3685 liter tank i Syrafast 316



155,000,00 kr /st exkl moms

Additional information: Chemistry; 4 support brackets made of Fe; 1 vessel with insulation (insulation jacket Fe, lacquered; diameter outside approx. 1780 mm); some residues of previous content; Metallic discolouration inside

Volumetric volume (L): 3.685 L



Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 65 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 347

Power: 1

Top: 7 mm

Cylinder: 5 mm

Bottom: 5 mm

Internal diameter tank: 1.600 mm

Total height of tank: 3.650 mm

SKU: 273580

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; 4 support brackets made of Fe; 1 vessel with insulation (insulation jacket Fe, lacquered; diameter outside approx. 1780 mm); some residues of previous content;Metallic discolouration

Övrig information2: inside; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3685

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.600 mm

Total höjd: 3.650 mm

Omrörare

Kraft (kW): 1

Varvtal: 347

Tjocklek på tank

Botten: 5 mm

Cylinder: 5 mm

Topp: 7 mm

Mer

Isolerad: Nej