370 liter tank i Syrafast 316



63 000 SEK /st exkl moms

Additional information: Handhole diameter: 350 mm; 2 dents in the insulation jacket; outlet with incomplete fittings
Volumetric volume (L): 370 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: available
Agitator: yes
Number of revolutions: 460

Power: 0,55
Internal diameter tank: 790 mm
Outer diameter tank: 900 mm
Total height of tank: 2.000 mm

SKU: 708055

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: vacuum
Konfiguration: insulated
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Handhole diameter: 350 mm; 2 dents in the insulation jacket; outlet with incomplete fittings; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 370

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 790 mm
Total höjd: 2.000 mm
Ytterdiameter: 900 mm

Omrörare
Kraft (kW): 0,55
Varvtal: 460

Mer
Isolerad: Ja