

38000 liter tank i Rostfritt 304



477 000 SEK /st exkl moms

Additional information: Chemistry; Stand frame made of Fe; manhole cover plated

Volumetric volume (L): 38.000 L

Pressure in tank: pressure

Max. pressure (Bar): 6 Bar

Max. temperature (°C): 165 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 1.087 L

Max Overpressure: 6 Bar

Max. working temperature: 165 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Agitator: yes

Power: 11,50

Top: 19 mm

Cylinder: 12 mm

Bottom: 16 mm

Internal diameter tank: 3.180 mm

Cylinder height: 3.900 mm

Total height of tank: 8.800 mm

SKU: 278572

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 165 °C

Mobil tank: Nej

Övrig information: Chemistry; Stand frame made of Fe; manhole cover plated; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 38000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 3.900 mm

Invändig diameter: 3.180 mm

Total höjd: 8.800 mm

Omrörare

Kraft (kW): 11,50

Tjocklek på tank

Botten: 16 mm

Cylinder: 12 mm

Topp: 19 mm

Mer

Isolerad: Nej