

## 3840 liter tank i Syrafast 316



**101 000 SEK /st exkl moms**

**Additional information:** According to the drawing, the vessel has a design pressure of -1/+3 bar, and the double jacket has a design pressure of 4 bar.; some residues of previous content

**Volumetric volume (L):** 3.840 L

**Pressure in tank:** ATM - atmospheric



**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 300 L

**Max Overpressure:** 2,50 Bar

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 130

**Agitator:** yes

**Number of revolutions:** 126

**Power:** 3

**Top:** 8,40 mm

**Cylinder:** 16 mm

**Bottom:** 5 mm

**Internal diameter tank:** 1.800 mm

**Outer diameter tank:** 1.900 mm

**Cylinder height:** 1.350 mm

**Total height of tank:** 4.250 mm

**SKU:** 705958



## Mer information

### Beskrivning av produkt

Material: Acid-resistant 316

Modell: Vertical

Nyttillverkad/Begagnad: Used

Arbetsstryck i tank: ATM – atmospheric

Konfiguration: single-skin

Mobil tank: No, it is not.

Övrig information: According to the drawing, the vessel has a design pressure of -1/+3 bar, and the double jacket has a design pressure of 4 bar.; some residues of previous content; we can't give any guarantees about

Övrig information2: the agitator

Omrörare: Yes

Total urtappning: Yes

Uppvärmning/kylning: No, it is not.

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3840

### Utrustning

Dokument finns: No, it is not.

Fläns för omrörare: No

Märkskylt: Yes

Teknisk ritning finns: No, it is not.

### Översikt material

Material: Acid-resistant 316



## Dimensioner av tank

Cylinderhöjd: 1.350 mm  
Invändig diameter: 1.800 mm  
Total höjd: 4.250 mm  
Ytterdiameter: 1.900 mm

## Omrörare

Kraft (kW): 3  
Varvtal: 126

## Tjocklek på tank

Botten: 5 mm  
Cylinder: 16 mm  
Topp: 8,40 mm

## Mer

Isolerad: No