

3900 liter tank i Syrafast 316



68 000 SEK /st exkl moms

Additional information: 4 support brackets made of stainless steel; some residues of previous content; motor-/gear is missing

Volumetric volume (L): 3.900 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 71 L

Max Overpressure: 2 Bar

Max. working temperature: 80 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN65 DIN 11851

Agitator: yes

Internal diameter tank: 1.590 mm

Outer diameter tank: 1.750 mm

Cylinder height: 1.550 mm

Total height of tank: 2.700 mm

SKU: 463437

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: 4 support brackets made of stainless steel; some residues of previous content; motor-/gear is missing; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3900

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.550 mm

Invändig diameter: 1.590 mm

Total höjd: 2.700 mm

Ytterdiameter: 1.750 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Ja