

39000 liter tank i Syrafast 316



298 000 SEK /st exkl moms

Additional information: 2 circumferential reinforcement/vacuum rings (80 mm wide); diameter including vacuum rings: approx. 3,160 mm

Volumetric volume (L): 39.000 L

Pressure in tank: vacuum



Min. pressure (Bar): 0,30 Bar

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: pipe end Ø appr. 65mm

Top: 5 mm

Cylinder: 5 mm

Bottom: 5,50 mm

Outer diameter tank: 3.000 mm

Cylinder height: 4.850 mm

Total height of tank: 6.600 mm

SKU: 703133

Mer information



Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: 2 circumferential reinforcement/vacuum rings (80 mm wide); diameter including vacuum rings: approx. 3,160 mm

Omrörare: Nej

Total urtappning: Ja

Undertryck (vakuum): 0,30 Bar

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 39000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 4.850 mm

Total höjd: 6.600 mm

Ytterdiameter: 3.000 mm



Tjocklek på tank

Botten: 5,50 mm

Cylinder: 5 mm

Topp: 5 mm

Mer

Isolerad: Nej