39000 liter tank i Syrafast 316



298 000 SEK /st exkl moms

Additional information: 2 circumferential reinforcement/vacuum rings (80 mm wide); diameter including vacuum rings: approx. 3,160 mm
Volumetric volume (L): 39.000 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 0,95 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,30 Bar

Max. temperature (°C): 95 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: pipe end Ø appr. 65mm
Top: 5 mm

Cylinder: 5 mm
Bottom: 5,50 mm
Outer diameter tank: 3.000 mm
Cylinder height: 4.850 mm
Total height of tank: 6.600 mm

SKU: 703133

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 95 °C
Mobil tank: Nej
Övrig information: 2 circumferential reinforcement/vacuum rings (80 mm wide); diameter including vacuum rings: approx. 3,160 mm
Omrörare: Nej
Övertryck: 0,95 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,30 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 39000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 4.850 mm
Total höjd: 6.600 mm
Ytterdiameter: 3.000 mm

Tjocklek på tank
Botten: 5,50 mm
Cylinder: 5 mm
Topp: 5 mm

Mer
Isolerad: Nej