

## 400 liter tank i Rostfritt 304



**57 000 SEK /st exkl moms**

**Additional information:** 1 dent in the insulation jacket; 1 oval metal cutout in the lid (see photos)

**Volumetric volume (L):** 400 L

**Pressure in tank:** ATM - atmospheric

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 160 L

**Max Overpressure:** 3 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** DN100 DIN 11851

**Agitator:** yes

**Number of revolutions:** 680 / 1370

**Power:** 0.7 / 1.1

**Internal diameter tank:** 740 mm

**Outer diameter tank:** 900 mm

**Total height of tank:** 2.250 mm

**SKU:** 484472

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: 1 dent in the insulation jacket; 1 oval metal cutout in the lid (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 400

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

### Dimensioner av tank

Invändig diameter: 740 mm

Total höjd: 2.250 mm

Ytterdiameter: 900 mm

**Omrörare**

Kraft (kW): 0.7 / 1.1

Varvtal: 680 / 1370

**Mer**

Isolerad: Ja