400 liter tank i Rostfritt 304



57 000 SEK /st exkl moms

Additional information: 1 dent in the insulation jacket; 1 oval metal cutout in the lid (see photos)
Volumetric volume (L): 400 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 150 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 160 L
Max Overpressure: 3 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Outlet of tank: DN100 DIN 11851
Agitator: yes
Number of revolutions: 680 / 1370
Power: 0.7 / 1.1
Internal diameter tank: 740 mm

Outer diameter tank: 900 mm
Total height of tank: 2.250 mm

SKU: 484472

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: 1 dent in the insulation jacket; 1 oval metal cutout in the lid (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 400

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 740 mm
Total höjd: 2.250 mm
Ytterdiameter: 900 mm

Omrörare
Kraft (kW): 0.7 / 1.1
Varvtal: 680 / 1370

Mer
Isolerad: Ja