400 liter tank i Rostfritt 304



96 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Volumetric volume (L): 400 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mobile tank: no

Top type: half hinging lid
Shape of tank: cylindrical
Bottom type: conical 15 °
Total discharge: yes
Fixation points: 3 adjustable feet

Type of HE on the cylinder: dimple-jacket
Position HE: the middle part of the cilinder
Height HE: 550 mm
Water pressure HE: 2 Bar
Type of HE on the bottom: dimple-jacket

Water pressure HE: 2 Bar
Heat exchanger: RVS 316
Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes
Documents included: no
Technical drawing included: yes
Registration plate on the tank: no

Flange for agitator: no
Tank outlet: inside Ø 72 mm
Outlet type: DIN11851
Agitator: yes
Agitator type: gate

Position engine: at the top
Number of revolutions: 21
Power: 1,50
Voltage: 400 V - three-phase
Top: 3 mm

Cylinder: 3 mm
Bottom: 3 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Cylinder: 2
Insulation bottom/sides: yes
finish of the outer jacket: welded

Insulation thickness: 40
Internal diameter tank: 850 mm
Distance from outlet to ground: 500 mm
Outer diameter tank: 1.020 mm
Cylinder height: 750 mm

Total height of tank: 2.100 mm
Empty weight tank: 650

SKU: 478575

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: isolert med varmeveksler
Mobil tank: Nej
Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: conical 15 °
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 400

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 72 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 750 mm
Invändig diameter: 850 mm
Mått utlopp till marken: 500 mm
Total höjd: 2.100 mm
Ytterdiameter: 1.020 mm

Värmeväxlare

Höjd värmeväxlare: 550 mm
Position värmeväxlare: the middle part of the cilinder
Typ av värmeväxlare på cylinder: dimple-jacket
Typ av värmeväxlare på botten: dimple-jacket
Vattentryck värmeväxlare: 2 Bar
Vattentryck värmeväxlare botten: 2 Bar

Omrörare

Kraft (kW): 1,50
Position motor: at the top
Typ av omrörare: gate
Varvtal: 21
Spänning (Volt): 400 V – three-phase

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isoleringsmaterial: Rockwool

Mer

Värmeväxlare: RVS 316
Cylinder OW: 2
Isoleringstjocklek OW: 40
Isolerad: Ja
Vikt: 650