

400 liter tank i Syrafast 316



179,000,00 kr /st exkl moms

Additional information: Pharmacy; Outlet extension slightly bent

Volumetric volume (L): 400 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 50 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 25

Agitator: yes

Number of revolutions: 1.410

Power: 1,50

Cylinder: 7,50 mm

Bottom: 5 mm

Internal diameter tank: 800 mm

Outer diameter tank: 950 mm

Cylinder height: 800 mm

Total height of tank: 2.500 mm

SKU: 284440

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; Outlet extension slightly bent; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 400

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 800 mm
Invändig diameter: 800 mm
Total höjd: 2.500 mm
Ytterdiameter: 950 mm

Omrörare

Kraft (kW): 1,50
Varvtal: 1.410

Tjocklek på tank

Botten: 5 mm
Cylinder: 7,50 mm

Mer

Isolerad: Ja