4000 liter tank i Rostfritt 304

244 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 4.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 adjustable feet

Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Position of manway: at the top
Hinged lid: yes
Agitator: yes
Agitator type: gate

Position engine: at the top
Number of revolutions: 10
Power: 1,10
Current: 2.9/5.0
Insulation thickness: 50

Outer diameter tank: 1.700 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Total height of tank: 3.900 mm

SKU: 411644

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 4000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank
Total höjd: 3.900 mm
Ytterdiameter: 1.700 mm

Omrörare
Kraft (kW): 1,10
Position motor: at the top
Typ av omrörare: gate
Varvtal: 10

Tjocklek på ytterbeklädnad och isolering
Isoleringsmaterial: Rockwool

Mer
Isoleringstjocklek OW: 50
Isolerad: Ja

Rodervägen 57
891 78 Bonässund
info@processoverskott.se