

4000 liter tank i Rostfritt 304



94 000 SEK /st exkl moms

Additional information: Vessel wired and primed on the outside; manhole diameter approx. 510 mm; 5 round connections in the lower bottom; 1 large dent in the insulation jacket; former connections in the upper bottom cut off (see photos)

Volumetric volume (L): 4.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: 100
Agitator: yes
Number of revolutions: 35,40
Power: 5,50
Internal diameter tank: 1.590 mm

Outer diameter tank: 1.800 mm
Cylinder height: 1.900 mm
Total height of tank: 3.200 mm

SKU: 309316

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: Tank blasted and primed on the outside; Manhole diameter approx. 510 mm; 5 round connections in the lower bottom; 1 strong dent in the insulation jacket; former connections in the upper bottom cut

Övrig information2: off (see photos) (see photos); we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 4000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.900 mm

Invändig diameter: 1.590 mm

Total höjd: 3.200 mm

Ytterdiameter: 1.800 mm

Omrörare

Kraft (kW): 5,50

Varvtal: 35,40

Mer

Isolerad: Ja