

## 4000 liter tank i Rostfritt 304



**93,000,00 kr /st exkl moms**

**Additional information:** Manhole diameter approx. 510 mm; 4 round openings and 1 further small opening in the lower bottom; the seam of the insulation jacket was slightly loose in one place (see photos)

**Volumetric volume (L):** 4.000 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 120 °C  
**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical  
**Configuration:** insulated  
**Heat exchanger:** no  
**Insulation:** yes  
**Mobile tank:** no

**Total discharge:** yes  
**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** yes  
**Flange for agitator:** no

**Position of manway:** headside  
**Outlet of tank:** 50  
**Agitator:** yes  
**Number of revolutions:** 35,30  
**Power:** 5,50

**Internal diameter tank:** 1.590 mm  
**Outer diameter tank:** 1.800 mm  
**Cylinder height:** 1.900 mm  
**Total height of tank:** 3.200 mm

**SKU:** 462489

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Max. arbetstemperatur: 120 °C

Mobil tank: Nej

Övrig information: Manhole diameter approx. 510 mm; 4 round openings and 1 further small opening in the lower bottom; the seam of the insulation jacket was slightly loose in one place (see photos); we can't give any

Övrig information2: guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 4000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 1.900 mm

Invändig diameter: 1.590 mm

Total höjd: 3.200 mm

Ytterdiameter: 1.800 mm

**Omrörare**

Kraft (kW): 5,50

Varvtal: 35,30

**Mer**

Isolerad: Ja