

4000 liter tank i Rostfritt 304



93 000 SEK /st exkl moms

Additional information: Manhole diameter approx. 510 mm; 4 round openings and 1 additional small opening in the underbody; the seam of the insulation jacket has come slightly loose in one place (see photos)

Volumetric volume (L): 4.000 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 120 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: headside
Outlet of tank: 50
Agitator: yes
Number of revolutions: 35,30
Power: 5,50

Internal diameter tank: 1.590 mm
Outer diameter tank: 1.800 mm
Cylinder height: 1.900 mm
Total height of tank: 3.200 mm

SKU: 462489

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Max. arbetstemperatur: 120 °C

Mobil tank: Nej

Övrig information: Manhole diameter approx. 510 mm; 4 round openings and 1 further small opening in the lower bottom; the seam of the insulation jacket was slightly loose in one place (see photos); we can't give any

Övrig information2: guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 4000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.900 mm

Invändig diameter: 1.590 mm

Total höjd: 3.200 mm

Ytterdiameter: 1.800 mm

Omrörare

Kraft (kW): 5,50

Varvtal: 35,30

Mer

Isolerad: Ja