

4000 liter tank i Syrafast 316



130 000 SEK /st exkl moms

Additional information: Dairy; Diameter manhole appr. 470 mm; if you are looking for an identical tank for this item, we may be able to offer you an identical tank from an external stock (without guarantee).

Volumetric volume (L): 4.000 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 2 Bar

Max. working temperature: 95 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN65

Agitator: yes

Number of revolutions: 29

Power: 0,55

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.600 mm

Outer diameter tank: 1.750 mm

Total height of tank: 4.100 mm

SKU: 273220

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Dairy; Diameter manhole appr. 470 mm; if you are looking for an identical tank for this item, we may be able to offer you an identical tank from an external stock (without guarantee).; we can't give

Övrig information2: any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 4000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.600 mm

Total höjd: 4.100 mm

Ytterdiameter: 1.750 mm

Omrörare

Kraft (kW): 0,55

Varvtal: 29

Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Mer

Isolerad: Ja