

40000 liter tank i Rostfritt 304



314 000 SEK /st exkl moms

Additional information: food industry; location: Belgium; 1 tank with slight differences in design (such as agitator 7,5 kW - 25/51 rpm); that tank with a dent in the insulation jacket; pipe end cut flush

Volumetric volume (L): 40.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: strong conical

Total discharge: yes

Fixation points: on skirt

Insulation material: rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: in the bottom

Tank outlet: inside Ø 100 mm

Outlet of tank: 100

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 12 / 23

Power: 2.7 / 5.5

Voltage: 380 V - three-phase

Insulation top: yes

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: welded

Distance from outlet to ground: 1.100 mm

Outer diameter tank: 3.850 mm

Total height of tank: 8.300 mm

Empty weight tank: 4.600

SKU: 265399

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nytilverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: food industry; location: Belgium; 1 tank with slight differences in design (such as agitator 7,5 kW – 25/51 rpm); that tank with a dent in the insulation jacket; pipe end cut flush; we can't give

Övrig information2: any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: strong conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 40000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 100 mm
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank

Mått utlopp till marken: 1.100 mm
Total höjd: 8.300 mm
Ytterdiameter: 3.850 mm

Omrörare

Kraft (kW): 2.7 / 5.5
Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 12 / 23
Spänning (Volt): 380 V – three-phase

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Isoleringsmaterial: Ja

Isolerad: Ja

Vikt: 4.600