40000 liter tank i Syrafast 316



839 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: strong conical bottom 35°; plate thickness10mm all around; AISI 316 with heavy 32kW agitator; we can't give any guarantees about the agitator
Volumetric volume (L): 40.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mobile tank: no

Top type: dished
Shape of tank: cylindrical
Bottom type: strong conical
Total discharge: yes
Fixation points: 4 non adjustable feet

Insulation material: Rockwool
Outer jacket (ornamental wall): aluminium
Manway(s): RVS 316
Fixation point(s): painted steel
Wet parts agitator(s): SS AISI 316 (V4A)

Suitable for food industry: no
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 600 mm
Agitator: yes
Agitator type: tripad

Position engine: at the top
Power: 32,50
Voltage: three-phase
Top: 10 mm
Cylinder: 10 mm

Bottom: 10 mm
Insulation thickness: 100
Outer diameter tank: 3.400 mm
Cylinder height: 7.200 mm
Total height of tank: 9.600 mm

SKU: 414017

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: strong conical bottom 35°; plate thickness10mm all around; AISI 316 with heavy 32kW agitator; we can’t give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: strong conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 40000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316
Fixeringspunkt(er): painted steel
Isoleringsmaterial: Rockwool
Material vätskeberörd del på omrörare: SS AISI 316 (V4A)
Ytterbeklädnad: aluminium

Dimensioner av tank
Cylinderhöjd: 7.200 mm
Total höjd: 9.600 mm
Ytterdiameter: 3.400 mm

Omrörare
Kraft (kW): 32,50
Position motor: at the top
Typ av omrörare: tripad
Spänning (Volt): three-phase

Tjocklek på tank
Botten: 10 mm
Cylinder: 10 mm
Topp: 10 mm

Tjocklek på ytterbeklädnad och isolering
Isoleringsmaterial: Rockwool

Mer
Isoleringstjocklek OW: 100
Isolerad: Ja