

40000 liter tank i Syrafast 316



827,000,00 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: strong conical bottom 35°; plate thickness 10mm all around; AISI 316 with heavy 32kW agitator; we can't give any guarantees about the agitator

Volumetric volume (L): 40.000 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no



Insulation: yes

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: strong conical

Total discharge: yes

Fixation points: 4 non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): aluminium

Manway(s): RVS 316

Fixation point(s): painted steel

Wet parts agitator(s): SS AISI 316 (V4A)

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 600 mm

Agitator: yes

Agitator type: tripod

Position engine: at the top

Power: 32,50

Voltage: three-phase

Top: 10 mm

Cylinder: 10 mm

Bottom: 10 mm

Insulation thickness: 100

Outer diameter tank: 3.400 mm

Cylinder height: 7.200 mm

Total height of tank: 9.600 mm

SKU: 290608

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: strong conical bottom 35°; plate thickness 10mm all around; AISI 316 with heavy 32kW agitator; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: strong conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 40000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Fixeringspunkt(er): painted steel

Isoleringsmaterial: Rockwool

Material vätskeberörd del på omrörare: SS AISI 316 (V4A)

Ytterbeklädnad: aluminium

Dimensioner av tank

Cylinderhöjd: 7.200 mm

Total höjd: 9.600 mm

Ytterdiameter: 3.400 mm

Omrörare

Kraft (kW): 32,50

Position motor: at the top

Typ av omrörare: tripad

Spänning (Volt): three-phase

Tjocklek på tank

Botten: 10 mm

Cylinder: 10 mm

Topp: 10 mm

Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: Rockwool

Mer

Isoleringstjocklek OW: 100

Isolerad: Ja