

420 liter tank i Syrafast 316



113,000,00 kr /st exkl moms

Additional information: pharmacy; One of the pressure tanks is sold with 3 load cells; pneumatic bottom drain valve mounted on the outlet; manhole diameter approx. 300 mm

Volumetric volume (L): 420 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 20 L

Max Overpressure: 6 Bar

Max. working temperature: 130 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: clamp

Agitator: yes

Number of revolutions: 2.820

Power: 0,55

Internal diameter tank: 785 mm

Cylinder height: 700 mm

Total outer width: 1.050 mm

Total outer length: 1.150 mm

SKU: 483266

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: pharmacy; One of the pressure tanks is sold with 3 load cells; pneumatic bottom drain valve mounted on the outlet; manhole diameter approx. 300 mm; we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 420

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 700 mm

Invändig diameter: 785 mm

Omrörare

Kraft (kW): 0,55

Varvtal: 2.820

Mer

Värmeväxlare: RVS 304

Isolerad: Ja