

## 420 liter tank i Syrafast 316



**113 000 SEK /st exkl moms**

**Additional information:** pharmacy; One of the pressure vessels is sold with 3 load cells; pneumatic bottom drain valve mounted at the outlet; manhole diameter approx. 300 mm

**Volumetric volume (L):** 420 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 130 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 20 L

**Max Overpressure:** 6 Bar

**Max. working temperature:** 130 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** clamp

**Agitator:** yes

**Number of revolutions:** 2.820

**Power:** 0,55

**Internal diameter tank:** 785 mm

**Cylinder height:** 700 mm

**Total outer width:** 1.050 mm

**Total outer length:** 1.150 mm

**SKU:** 483266

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: pharmacy; One of the pressure tanks is sold with 3 load cells; pneumatic bottom drain valve mounted on the outlet; manhole diameter approx. 300 mm; we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 420

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

**Dimensioner av tank**

Cylinderhöjd: 700 mm

Invändig diameter: 785 mm

**Omrörare**

Kraft (kW): 0,55

Varvtal: 2.820

**Mer**

Värmeväxlare: RVS 304

Isolerad: Ja