420 liter tank i Syrafast 316



113 000 SEK /st exkl moms

Additional information: pharmacy; One of the pressure vessels is sold with 3 load cells; pneumatic bottom drain valve mounted at the outlet; manhole diameter approx. 300 mm
Volumetric volume (L): 420 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 20 L
Max Overpressure: 6 Bar

Max. working temperature: 130 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 316
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: clamp

Agitator: yes
Number of revolutions: 2.820
Power: 0,55
Internal diameter tank: 785 mm
Cylinder height: 700 mm

Total outer width: 1.050 mm
Total outer length: 1.150 mm

SKU: 483266

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 130 °C
Mobil tank: Nej
Övrig information: pharmacy; One of the pressure tanks is sold with 3 load cells; pneumatic bottom drain valve mounted on the outlet; manhole diameter approx. 300 mm; we can't give any guarantees about the
Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 420

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 700 mm
Invändig diameter: 785 mm

Omrörare
Kraft (kW): 0,55
Varvtal: 2.820

Mer
Värmeväxlare: RVS 304
Isolerad: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se