

42200 liter tank i GAP/Plast



96,000,00 kr /st exkl moms

Article type: second-hand storage tank

Volumetric volume (L): 42.200 L

Max. density P (kg/m³): 1.300

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 30 °C

Min. temperature (°C): -20 °C

Material wet parts: polyester (fiberglass)

Model: vertical

Configuration: insulated



Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: flat

Total discharge: no

Fixation points: 6 attachment points

Insulation material: PUR

Suitable for food industry: no

Documents included: no

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: yes

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 600 mm

Tank outlet: outside Ø 100 mm

Agitator: no, optional

Insulation thickness: 30

Tank capacity top cylinder: 42.200 L

Internal diameter tank: 3.000 mm

Distance from outlet to ground: 500 mm

Outer diameter tank: 3.190 mm

Total height of tank: 6.260 mm

Total outer width: 3.190 mm

SKU: 196391



Mer information

Beskrivning av produkt

Material: GAP/Plast
Modell: Vertikal
Nyttillverkad/Begagnad: Begagnad
Arbetsstryck i tank: ATM – atmosferic
Konfiguration: insulated
Max. arbetstemperatur: 30 °C
Maximal densitet för produkten: 1300
Min. arbetstemperatur: -20 °C
Mobil tank: Nej
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Nej
Typ av botten: flat
Uppvärmning/kylning: Nej
Vätskeberörd yta: polyester (fiberglass)
Volym i liter: 42200

Utrustning

Dokument finns: Nej
Fläns för omrörare: Ja
Märkskylt: Ja
Tankutlopp: outside Ø 100 mm
Teknisk ritning finns: Ja

Översikt material

Material: GAP/Plast
Isoleringsmaterial: PUR

**Dimensioner av tank**

Invändig diameter: 3.000 mm

Mått utlopp till marken: 500 mm

Total höjd: 6.260 mm

Ytterdiameter: 3.190 mm

Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: PUR

Mer

Isoleringstjocklek: 30

Isoleringstjocklek OW: 30

Isolerad: Ja