

## 42200 liter tank i GAP/Plast



**95 000 SEK /st exkl moms**

**Article type:** second-hand storage tank

**Volumetric volume (L):** 42.200 L

**Max. density P (kg/m<sup>3</sup>):** 1.300

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 30 °C

**Min. temperature (°C):** -20 °C

**Material wet parts:** polyester (fiberglass)

**Model:** vertical

**Configuration:** insulated



**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Top type:** dished

**Shape of tank:** cylindrical

**Bottom type:** flat

**Total discharge:** no

**Fixation points:** 6 attachment points

**Insulation material:** PUR

**Suitable for food industry:** no

**Documents included:** no

**Technical drawing included:** yes

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** cylinder

**Height manhole 1 (mm):** 600 mm

**Tank outlet:** outside Ø 100 mm

**Insulation top:** yes

**Insulation body:** yes

**Insulation thickness:** 30

**Tank capacity top cylinder:** 42.200 L

**Internal diameter tank:** 3.000 mm

**Distance from outlet to ground:** 500 mm

**Outer diameter tank:** 3.190 mm

**Total height of tank:** 6.260 mm

**Total outer width:** 3.190 mm

**Empty weight tank:** 3.000

**SKU:** 196460

## Mer information

### Beskrivning av produkt

Material: GAP/Plast  
Modell: Vertikal  
Nyttillverkad/Begagnad: Begagnad  
Arbetstryck i tank: ATM – atmosferic  
Konfiguration: insulated  
Max. arbetstemperatur: 30 °C  
Maximal densitet för produkten: 1300  
Min. arbetstemperatur: -20 °C  
Mobil tank: Nej  
Omrörare: Nej  
Tankens form: cylindrical  
Total urtappning: Nej  
Typ av botten: flat  
Uppvärmning/kylning: Nej  
Vätskeberörd yta: polyester (fiberglass)  
Volym i liter: 42200

### Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Ja  
Tankutlopp: outside Ø 100 mm  
Teknisk ritning finns: Ja

### Översikt material

Material: GAP/Plast  
Isoleringsmaterial: PUR

## Dimensioner av tank

Invändig diameter: 3.000 mm  
Mått utlopp till marken: 500 mm  
Total höjd: 6.260 mm  
Ytterdiameter: 3.190 mm

## Tjocklek på ytterbeklädnad och isolering

Isolering mantel: Ja  
Isoleringsmaterial: PUR

## Mer

Isoleringsmaterial: Ja  
Isoleringstjocklek OW: 30  
Isolerad: Ja  
Vikt: 3.000