435 liter tank i Syrafast 316



100 000 SEK /st exkl moms

Additional information: 1 dent in the inner cylinder (overpressure double jacket; see photos)
Volumetric volume (L): 435 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 143 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 42 L
Max Overpressure: 2 Bar

Max. working temperature: 143 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: yes
Outlet of tank: 37
Internal diameter tank: 770 mm
Outer diameter tank: 940 mm

Cylinder height: 670 mm
Total height of tank: 1.650 mm

SKU: 429806

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 143 °C
Mobil tank: Nej
Övrig information: Pharmacy; 1 dent in the inner cylinder (overpressure double jacket; see photos); we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 435

Utrustning

Dokument finns: Nej
Fläns för omrörare: Ja
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 670 mm
Invändig diameter: 770 mm
Total höjd: 1.650 mm
Ytterdiameter: 940 mm

Mer
Isolerad: Ja