

## 4370 liter tank i Syrafast 316



**102 000 SEK /st exkl moms**

**Article type:** second-hand pressure tank

**Additional information:** we can't give any guarantees about the agitator

**Volumetric volume (L):** 4.370 L

**Pressure in tank:** pressure

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** -1 Bar

**Max. temperature (°C):** 200 °C

**Min. temperature (°C):** -30 °C

**Material wet parts:** SS AISI 316 (V4A)



**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Top type:** dished

**Shape of tank:** cylindrical

**Bottom type:** dished

**Total discharge:** yes

**Fixation points:** 3 non adjustable feet

**Fixation point(s):** painted steel

**Suitable for food industry:** no

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** cylinder

**Height manhole 1 (mm):** 500 mm

**Tank outlet:** inside Ø 80 mm

**Total outlet valve:** no

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** in the cylinder

**Number of revolutions:** 955

**Power:** 4,30

**Voltage:** three-phase

**Top:** 8 mm

**Cylinder:** 6 mm

**Bottom:** 6 mm

**Distance from outlet to ground:** 70 mm

**Outer diameter tank:** 1.780 mm

**Cylinder height:** 1.250 mm

**Total height of tank:** 2.360 mm

**Empty weight tank:** 1.500

**SKU:** 88359

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Min. arbetstemperatur: -30 °C

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Undertryck (vakuum): -1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 4370



## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Ja  
Tankutlopp: inside Ø 80 mm  
Teknisk ritning finns: Nej  
Utloppsventil: Nej

## Översikt material

Material: Syrafast 316  
Fixeringspunkt(er): painted steel

## Dimensioner av tank

Cylinderhöjd: 1.250 mm  
Mått utlopp till marken: 70 mm  
Total höjd: 2.360 mm  
Ytterdiameter: 1.780 mm

## Omrörare

Kraft (kW): 4,30  
Position motor: in the cylinder  
Typ av omrörare: propeller agitator  
Varvtal: 955  
Spänning (Volt): three-phase

## Tjocklek på tank

Botten: 6 mm  
Cylinder: 6 mm  
Topp: 8 mm

## Mer

Isolerad: Nej  
Vikt: 1.500

