

4413 liter tank i Syrafast 316



243 000 SEK /st exkl moms

Additional information: Half-pipe coil only in the upper area of the cylinder and on the underbody;
manhole diameter: 500 mm

Volumetric volume (L): 4.413 L

Pressure in tank: vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 116 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 203

Power: 2,20

Top: 7,20 mm

Cylinder: 6,20 mm

Bottom: 6,20 mm

Internal diameter tank: 1.790 mm

Cylinder height: 1.250 mm

Total height of tank: 2.890 mm

Empty weight tank: 1.250

SKU: 488181

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Half-pipe coil only in the upper part of the cylinder and on the bottom;
manhole diameter: 500 mm; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 4413

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.250 mm

Invändig diameter: 1.790 mm

Total höjd: 2.890 mm

Omrörare

Kraft (kW): 2,20

Varvtal: 203

Tjocklek på tank

Botten: 6,20 mm

Cylinder: 6,20 mm

Topp: 7,20 mm

Mer

Isolerad: Nej

Vikt: 1.250