4413 liter tank i Syrafast 316



244 000 SEK /st exkl moms

Additional information: Half-pipe coil only in the upper area of the cylinder and on the underbody; manhole diameter: 500 mm
Volumetric volume (L): 4.413 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 116 L
Max Overpressure: 16 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: cylinder
Outlet of tank: flange DN80

Agitator: yes
Number of revolutions: 203
Power: 2,20
Top: 7,20 mm
Cylinder: 6,20 mm

Bottom: 6,20 mm
Internal diameter tank: 1.790 mm
Cylinder height: 1.250 mm
Total height of tank: 2.890 mm
Empty weight tank: 1.250

SKU: 488181

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Half-pipe coil only in the upper part of the cylinder and on the bottom; manhole diameter: 500 mm; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 4413

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.250 mm
Invändig diameter: 1.790 mm
Total höjd: 2.890 mm

Omrörare
Kraft (kW): 2,20
Varvtal: 203

Tjocklek på tank
Botten: 6,20 mm
Cylinder: 6,20 mm
Topp: 7,20 mm

Mer
Isolerad: Nej
Vikt: 1.250