44480 liter tank i Syrafast 316



304 000 SEK /st exkl moms

Additional information: Double-chamber storage tank divided into two 22,240 liter tanks; total height as per drawing, cylindrical height of each 22,240 liter tank as per drawing
Volumetric volume (L): 44.480 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 1 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,25 Bar

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN100
Top: 6 mm

Cylinder: 6 mm
Bottom: 10 mm
Internal diameter tank: 3.200 mm
Cylinder height: 1.930 mm
Total height of tank: 7.380 mm

SKU: 476707

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Double-chamber storage tank divided into two 22.240 liter tanks; total height as per drawing, cylindrical height of each 22.240 liter tank as per drawing
Omrörare: Nej
Övertryck: 1 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,25 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 44480

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.930 mm
Invändig diameter: 3.200 mm
Total höjd: 7.380 mm

Tjocklek på tank
Botten: 10 mm
Cylinder: 6 mm
Topp: 6 mm

Mer
Isolerad: Nej