4450 liter tank i Rostfritt 304



155 000 SEK /st exkl moms

Article type: second-hand pressure tank
Additional information: Tank AD-2000 Merkblatt; hardly ever used
Volumetric volume (L): 4.450 L
Max. density P (kg/m³): 1.200
Pressure in tank: pressure

Max. pressure (Bar): 0,50 Bar
Max. temperature (°C): 90 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: single-skin

Heat exchanger: no

Insulation: no
Mobile tank: no
Top type: dished
Shape of tank: cylindrical

Bottom type: dished
Total discharge: yes
Fixation points: 4 non adjustable feet
Manway(s): RVS 304
Fixation point(s): RVS 304

Suitable for food industry: no
Documents included: yes
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no

Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 500 mm
Tank outlet: inside Ø 50 mm
Agitator: no

Top: 5 mm
Cylinder: 4 mm
Bottom: 5 mm
Outer diameter tank: 1.800 mm
Cylinder height: 1.585 mm

Total height of tank: 2.400 mm
Empty weight tank: 805

SKU: 417953

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Max. arbetstemperatur: 90 °C
Maximal densitet för produkten: 1200
Mobil tank: Nej
Övrig information: Tank AD-2000 Merkblatt; hardly ever used
Omrörare: Nej
Övertryck: 0,50 Bar
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: dished
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 4450

Utrustning

Dokument finns: Ja
Fläns för omrörare: Nej
Märkskylt: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Ja

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank
Cylinderhöjd: 1.585 mm
Total höjd: 2.400 mm
Ytterdiameter: 1.800 mm

Tjocklek på tank
Botten: 5 mm
Cylinder: 4 mm
Topp: 5 mm

Mer
Isolerad: Nej
Vikt: 805

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se